

# CELL POWER

## CESS 372

CESS 372 is the perfect scalable energy storage system. The Energy Storage System is a cutting-edge solution designed to revolutionize the way energy is stored and utilized.

With a high energy density of 372 kWh in a relatively small cabinet, the ESS boasts a compact and space-efficient design, optimizing its footprint while ensuring maximum storage capacity. The ESS is built with Lithium Iron Phosphate (LFP) batteries, renowned for their exceptional safety and longevity. With an impressive lifespan of 6000 cycles, the batteries offer sustained reliability, making them an ideal choice for long-term energy storage needs. With the ability to seamlessly integrate additional modules, the system can be easily scaled up to meet growing energy storage requirements, making it



an ideal choice for both current and future needs. Safety is a paramount topic, the ESS addresses this with a fire suppression system, extensive certifications and the use of one of the safest battery technologies: LFP. This system significantly reduces the risk of fire by actively monitoring and suppressing any potential hazards, providing added peace of mind and safeguarding the integrity of the stored energy. Maintenance of the ESS is made easy with its accessible design, allowing for convenient and safe inspection, servicing, and troubleshooting.



### Superior Quality

Highly compact cabinets and containers with LFP technology offer superior energy density. Long-life:  $\geq 6000$  cycles and 15 years expectancy (70% EOL).



### Extensive Experience

Over 35 years of battery knowledge and 10+ years of experience with lithium technology. Expert in manufacturing custom-made energy storage systems.



### Turnkey systems


We deliver our systems plug-and-play. This means pre-assembling, pre-testing, and full integration of all the components in the Netherlands. <1 day installation time.




### Robust safety

Ultimate protection due to superior thermal stability, dual fire protection safeguards (battery pack and cabinet). PGS 37-1 compliant.

## Possible applications



**SELF-CONSUMPTION  
OPTIMISATION**



**PEAK-SHAVING**



**TRADING**

# CELL POWER

**CESS 372**



## GENERAL INFORMATION

Dimensions (LxWxH)	1300 x 1300 x 2374 mm
Weight	~3850kg
Housing	Outdoor cabinet
Anti corrosion level	C5
Noise level	≤75dB
Protection rating	IP55
Operating temperature	-30°C ~ +50°C
Relative humidity	20% ~ 85% (Non-condensing)
Maximum operating altitude	2000m (No derating)
Thermal management system	Liquid cooling
EMS functionality	Depends on EMS
Communication interface	CAN, MODBUS TCP/RTU
Off-grid capability	Depends on PCS

## BATTERY

Battery technology	LFP (LiFePO4/ Lithium Iron Phosphate)
Nominal Energy	372,7 kWh
Nominal Capacity	280 Ah
Nominal Voltage	1331,2V
Voltage range (min. - Max.)	1164,8 ~ 1497,6V
Cycle life @0.5C / 25°C	≥6000 cycles
DoD	90%

## SAFETY

Fire suppression system	Double (batterypack and cabinet) fire suppression system
-------------------------	--

## INVERTER

Compatible with CBI 215-1725
------------------------------

## WARRANTY & CERTIFICATES

Warranty	5 years
Certificates battery	UN38.3; IEC 62619; UL 9540A
Certificates inverter	n.v.t.

## EXAMPLE CONFIGURATIONS

2 pcs	744 kWh
3 pcs	1116 kWh
4 pcs	1488 kWh
x pcs in parallel maximum	2236 kWh
6 pcs to one PCS maximum	

